

DESCRIPTION

CATALOG: E-758-T-232-HL	BALLAST TYPE: Electronic	STARTING METHOD: Instant Start	NUMBER OF LAMPS - LAMP TYPE: 1-F25T8, 1-F32T8, 1-F32T8/U, 2-F17T8, 2-F25T8, 2-F32T8, 2-F32T8/U
-----------------------------------	------------------------------------	--	--

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE: 277 V~ ±10%	LAMP WATTS: 17/25/32 W	INPUT WATTS: 76 W	INPUT CURRENT: 0.28 A	OCV: 610 V	PF: > 0.97	FREQUENCY: 60 Hz	SOUND RATED: A
MIN START TEMP: 32°F / 0°C	CLASS: P	TYPE: 1 outdoor	BALLAST FACTOR: 1.17	BEF: 1.53	LAMP CONNECTION: PARALLEL	THD (1): < 19%	NO PCB'S

(1) FOR 2-F32T8

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	1.68	8.90	8.34	2.37	9.50	1.50
	TOL(+/-)	0.01	0.01	0.01	0.05	0.05	0.05
	MM	43	226	212	60	241	38
	TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	BLUE		
INCHES	22	22	36	26	26		
TOL(+/-)	3/8	3/8	3/8	3/8	3/8		
MM	559	559	914	660	660		
TOL(+/-)	10	10	10	10	10		

CARTON CHARACTERISTICS


UNITS/CARTON 10	CARTONS/LAYER 12	# OF LAYERS 8	UNITS/PALLET 960	PIECE WEIGHT 2.5 lbs	CARTON WEIGHT 26 lbs	PALLET WEIGHT 2,573 lbs
CARTONS/PALLET 96	CARTON DIMENSIONS 12" x 12" x 4"		PALLET DIMENSIONS 40" x 48" x 7"		PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 40"	

MISC.

--

CARTON LABEL

ELECTRICAL DIAGRAM



PRODUCT LABEL



ISO 9001:2000



Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.

ISB LPS, LP
2840 Keller Springs Road,
Suites 1102 & 1103
Carrollton, Tx. 75006-4832
Tel. (972) 416-4500
Fax. (972) 418-5858