

DESCRIPTION

CATALOG: E420-T-234-SW		STARTING METHOD: Rapid Start	INPUT VOLTAGE: 277 V~	OCV: 290 V~	FREQUENCY: 60 Hz
BALLAST TYPE: Energy efficient magnetic	CLASS: P	TYPE: 1 outdoor	LAMP CONNECTION: Series	SOUND RATED: A NO PCB'S	

ELECTRICAL CHARACTERISTICS

LAMP TYPE	NUMBER OF LAMPS	LAMP WATTS	MIN. START TEMP. (°F/°C)	INPUT WATTS (Watts)	INPUT CURRENT (Amps)	BALLAST FACTOR	B.E.F.	P.F.	THD %	LAMP CREST FACTOR
F40T12	2	40	50/10	89	0.34	0.94	1.055	0.94	12	1.6
F40T12/ES	2	34	60/16	77	0.29	0.89	1.155	0.96	13	1.8
F40T12/U	2	40	50/10	89	0.33	0.94	1.055	0.97	12	1.5
F40T12/U/ES	2	34	60/16	77	0.29	0.89	1.155	0.96	13	1.8
F40T10	2	40	50/10	90	0.35	0.94	1.045	0.93	13	1.5

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	1.687	8.906	8.344	2.375	9.5	1.5
	TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.050
	MM	43	226	212	60	241	38
	TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	YELLOW		
INCHES	22	22	12	12	12		
TOL(+/-)	3/8	3/8	3/8	3/8	3/8		
MM	559	559	305	305	305		
TOL(+/-)	10	10	10	10	10		

CARTON CHARACTERISTICS

UNITS/CARTON: 10	CARTON/LAYER: 12	# OF LAYERS: 5	UNITS PALLET: 600	PIECE WEIGHT: 3.5 lbs	CARTON WEIGHT: 36 lbs	PALLET WEIGHT: 2 195 lbs
CARTON PALLET: 60	CARTON DIMENSIONS: 12" x 12" x 4"		PALLET DIMENSIONS: 40" x 48" x 7"		PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET: 40" x 48" x 27"	


MISC.

For Replacement Use Only; Shrink Wrapped Individual Units.

CARTON LABEL



ELECTRICAL DIAGRAM



PRODUCT LABEL



Certificate No. 008281

Lighting and Power Source
 2840 Keller Springs Road,
 Suite 1102 & 1103
 Carrollton, TX 75006 – 4832
 Tel: (888) 385-4448
 Fax: (972) 418-5858

Made in Mexico by Industrias Sola Basic S.A. de C.V.