

DESCRIPTION

CATALOG: ETSF-20-TP		STARTING METHOD: Trigger Start	INPUT VOLTAGE: 120 V~	OCV: 215 V~	FREQUENCY: 60 Hz
BALLAST TYPE: Normal Power Factor	CLASS: P	TYPE: 1 outdoor	LAMP CONNECTION: Series	SOUND RATED: A NO PCB'S	

ELECTRICAL CHARACTERISTICS

LAMP TYPE	NUMBER OF LAMPS	LAMP WATTS	MIN. START TEMP. (°F/°C)	INPUT WATTS (Watts)	INPUT CURRENT (Amps)	BALLAST FACTOR	B.E.F.	P.F.	THD %	LAMP CREST FACTOR
F20T12	1	20	50/10	33	0.65	0.83	2.530	0.42	8	1.6
F15T12	1	15	50/10	33	0.69	0.98	3.015	0.39	8	1.7
F14T12	1	14	50/10	32	0.70	0.91	2.879	0.37	9	1.7
F15T8	1	15	50/10	32	0.69	0.95	2.968	0.38	7	1.6
F14T8	1	14	50/10	30	0.70	0.95	3.166	0.36	6	1.5

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	H	
	INCHES	N/A	6.0	5.275	1.937	6.5	1.375
	TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.150
	MM	N/A	153	134	49	165	35
	TOL(+/-)	0.25	0.25	0.25	1.30	1.30	3.80
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	YELLOW		
INCHES	12	12	13	13			
TOL(+/-)	3/8	3/8	3/8	3/8			
MM	304	304	330	330			
TOL(+/-)	10	10	10	10			

CARTON CHARACTERISTICS

UNITS/CARTON: 16	CARTON/LAYER: 12	# OF LAYERS: 5	UNITS PALLET: 960	PIECE WEIGHT: 2.3 lbs	CARTON WEIGHT: 38 lbs	PALLET WEIGHT: 2 364 lbs
CARTON PALLET: 60	CARTON DIMENSIONS: 12" x 12" x 4"		PALLET DIMENSIONS: 40" x 48" x 7"		PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET: 40" x 48" x 28"	


MISC.

Use Circuit-Interrupting Lamp Holder.

CARTON LABEL



ELECTRICAL DIAGRAM



PRODUCT LABEL



Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



Certificate No. 008281

Lighting and Power Source
 2840 Keller Springs Road,
 Suite 1102 & 1103
 Carrollton, TX 75006 – 4832
 Tel: (888) 385-4448
 Fax: (972) 418-5858

Made in Mexico by Industrias Sola Basic S.A. de C.V.